

SELF-BUNDED FUEL TANKS CONTAINERISED RANGE

Our large above ground tank capacities range from 12,000 to 100,000 Litres. As the tanks are designed to the ISO container footprints, the transportation and handling of liquids is made safe and easy. Paint protection allows the tank to withstand harsh environments. These tanks are ideal for multiple applications in the Heavy Industry such as Construction, Logistics, Agriculture, and Mining.

FUEL STORAGE COMPATIBILITY ODiesel ODunleaded ODubricants ODKerosene

FEATURES

- Mild steel internal tank and wetted parts heavy duty mild steel external tank.
- AS1940 approved for the handling and storage of flammable and combustible liquids.
- AS1692 approved for steel tanks containing flammable and combustible liquids.
- Self-bunded to facilitate leaks: 100% Primary Tank + 10% interstitial space = 110% bunded tank.
- Forklift pockets and stress and strength tested lifting tie points at each corner.
- Paint protection for harsh environments.
- Manway tank access points via two manholes.

SDI Tanks

- Updraft vent pipe.
- Aluminium anodised dipstick / level gauge.
- Interstitial space monitoring point with anodised dip stick.
- Overfill protection alarm.
- Transportable via tilt tray or flatbed semi-trailer.

12 MONTH WARRANTY STANDARDS Australia Australia

soi Tanks

SPECIFICATIONS

MODEL	LENGTH (mm)	WIDTH (mm)	HEIGHT (mm)	SFL (L)	TARE WEIGHT (kg)
12,000L	3,058	2,438	2,896	11,912	4,500
30,000L	6,056	2,438	2,896	28,758	7,500
65,000L	12,192	2,438	2,896	62,385	13,100
80,000L	14,630	2,438	2,896	76,850	15,750
100,000L	14,630	2,438	3,650	103,661	16,650

PUMP BAY & ACCESSORIES (SOLD SEPARATELY)

Attachable pump bay modules available for purchase separately.

- AS1657 approved for walkway and ladders.
- Lockable bund doors with rubber dust seal.

Built in safety handrail system and access ladder.

Pump bays can be customised with accessories such as:

Pumps Hoses Filters Fuel Management Systems

FITTINGS

Fill Line with Camlock Male Fitting with Dust Cap, Fire Safe Ball Valve & Wafer Style Return Valve

Suction Outlet with Fire Safe Ball Valve

- Spare Connections
- Anodised Dipsticks (Fuel Dip, Interstitial Dip)
- Set of Statutory Signage2 x 2" Suction Connection



08 9399 2511 info@steeldale.com.au

CONTACT US TODAY

